<b>M1.</b> (a)	(i)	meter deflects then returns to zero ✓ current produces (magnetic) field / flux ✓ change in field / flux through Q induces emf ✓ induced emf causes current in Q (and meter) ✓
		Deflection to right (condone left) then zero is equivalent to 1st mark.
		Accept momentary deflection for 1 <sup>st</sup> point.
		"Change in field / flux <u>induces</u> current in Q" is just 🖌 from the last two marking points.

max 3

(ii) meter deflects in opposite direction (or to left, or ecf) ✓ field / flux through P is reduced ✓ induces emf / current in opposite direction ✓ Ignore references to magnitude of deflection.

2

(b) (i) flux linkage (= 
$$n\Phi = nBA$$
) = 40 × 0.42 × 3.6 × 10<sup>-3</sup>  
= 6.0(5) × 10<sup>-2</sup> ✓

Unit mark is independent. Allow  $6 \times 10^{-2}$ .

Wb turns ✓ Accept 60 mWb turns if this unit is made clear. Unit: allow Wb.

(ii) change in flux linkage =  $\Delta(n\Phi)$ = 6.05 × 10<sup>-2</sup> (Wb turns)  $\checkmark$ induced emf  $\left(=\frac{\Delta(n\phi)}{\Delta t}\right) = \frac{6.05 \times 10^{-2}}{0.50} = 0.12(1)$  (V)  $\checkmark$ 

Essential to appreciate that  $6.05 \times 10^{-2}$  is change in flux linkage for 1<sup>st</sup> mark. Otherwise mark to max 1.

[9]

2

M3.(a) (i) 60 (degrees) 🗸

(ii) angle required is 150° ✓

2

1

1

(b) (i) (magnitude of the induced) emf ✓
Accept "induced voltage" or "rate of change of flux linkage", but not "voltage" alone.

(ii) frequency 
$$\left(=\frac{1}{T}\right) = \frac{1}{40 \times 10^{-3}} \checkmark (= 25 \text{ Hz})$$

no of revolutions per minute =  $25 \times 60 = 1500$  1500 scores both marks. Award 1 mark for  $40s \rightarrow 1.5$  rev min<sup>-1</sup>.

2

(iii) maximum flux linkage (=BAN) = 0.55 (Wb turns) ✓

angular speed  $\omega \left(=\frac{2\pi}{T}\right) = \frac{2\pi}{40 \times 10^{-3}} \checkmark (= 157 \text{ rad s}^{-1})$